

Philips
PAL coax cable

2 m

Black Right angle

SWV2832W



Ensure a reliable connection

with this PAL type coaxial cable

Depend on this cable to provide you with a reliable audio/video connection between components.

Enjoy good picture quality

- Nickel-plated connectors for reliable contact

Enjoy good audio quality

- High purity copper conductor for reliable signal transfer

Protects against signal loss

- Bare copper shielding

Easy installation

- Non-slip ergonomic grip for easy use

Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

PHILIPS
sense and simplicity

PAL coax cable
2 m Black Right angle

Specifications

Packaging dimensions

- **Packaging dimensions (W x H x D):**
9.4 x 23.6 x 3.6 cm
- **Nett weight:** 0.158 kg
- **Gross weight:** 0.180 kg
- **Tare weight:** 0.022 kg
- **EAN:** 87 12581 38067 0
- **Number of products included:** 1
- **Packaging type:** Blister

Outer Carton

- **Outer carton (L x W x H):** 33.0 x 25.7 x 17.8 cm
- **Nett weight:** 1.896 kg

- **Gross weight:** 2.040 kg
- **Tare weight:** 0.144 kg
- **EAN:** 87 12581 38069 4
- **Number of consumer packagings:** 12

Inner Carton

- **Inner carton (L x W x H):** 24.4 x 10.4 x 16.0 cm
- **Nett weight:** 0.632 kg
- **Gross weight:** 0.712 kg
- **Tare weight:** 0.080 kg
- **EAN:** 87 12581 38068 7
- **Number of consumer packagings:** 4

SWV2832W/I0

Product highlights

Bare copper shielding

Bare copper shielding protects against signal loss.

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.

Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

Nickel-plated connectors

Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.



Issue date 2008-10-19

Version: 1.1.5

12 NC: 8670 000 35477
EAN: 87 12581 38067 0

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips
Electronics N.V. or their respective owners.

www.philips.com